

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS

FORA™- Form Oil Release Agent

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

SAFETY-KLEEN PROFESSIONAL PRODUCTS

FORATM - Form Oil Release Agent

Product Code

Not available.

Recommended Use

Form oil release agent. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

None known.

MANUFACTURER/SUPPLIER

Safety-Kleen Systems, Inc.

2600 North Central Expressway

Suite 200

Richardson, TX 75080 www.safety-kleen.com

IMPORTER/DISTRIBUTOR

Safety-Kleen Canada, Inc.

25 Regan Road

Brampton, Ontario, Canada L1A 1B2

SDS ID: 820256

Phone: 1-800-669-5740 Emergency Phone #: 1-800-468-1760

Issue Date

April 25, 2017

Supersedes Issue Date

July 15, 2016

Original Issue Date

July 15, 2016

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR) (SOR/2015-17)

None needed according to classification criteria

GHS Label Elements

Symbol(s)

None needed according to classification criteria

Signal Word

None needed according to classification criteria

Hazard Statement(s)

None needed according to classification criteria.

Precautionary Statement(s)

Prevention

None needed according to classification criteria.

Response

None needed according to classification criteria.

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS FORA™- Form Oil Release Agent

Other hazards

No information available.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

SDS ID: 820256

CAS	Component Name	Percent		
64742-53-6	Petroleum distillates, hydrotreated light naphthenic	90-99		

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention if needed.

Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if needed.

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get medical attention if needed.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most Important Symptoms/Effects

Acute

No information on significant adverse effects.

Delayed

Repeated exposure may cause skin dryness or cracking.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Water spray, fog, carbon dioxide, regular dry chemical, alcohol resistant foam

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Slight fire hazard. Decomposition and combustion materials may be toxic.

Hazardous Combustion Products

Carbon monoxide.

Fire Fighting Measures

Keep storage containers cool with water spray. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Do not scatter spilled material with high-pressure water streams. Apply water from a protected location or from a safe distance. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Dike for later disposal.

Page 2 of 8 Rev. 04/17

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS FORA™- Form Oil Release Agent

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

SDS ID: 820256

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8, Exposure Controls/Personal Protection.

Methods and Materials for Containment and Cleaning Up

Stop leak if possible without personal risk. Provide adequate ventilation. Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements, or confined areas. Collect spilled material in appropriate container for disposal. Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Use in accordance with good industrial hygiene practices. Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and naked flames. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Do not mix with incompatible materials. Product is slippery. If product is spilled onto floor, clean area to prevent slipping.

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

Incompatible Materials

Incompatible materials include acids, strong oxidizing materials, chlorine, concentrated oxygen, calcium hypochlorite, sodium hypochlorite.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada, ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions

Page 3 of 8 Rev. 04/17

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS FORA™- Form Oil Release Agent

warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

SDS ID: 820256

Glove Recommendations

Where skin contact is likely, wear neoprene, nitrile, or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, and lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid	Physical State	Liquid			
Odor	Mild ,petroleum odor	Color	Not available			
Odor Threshold	Not available	pН	Not available			
Melting Point	-48 °C (-54.4 °F)	Boiling Point	260 - 370 °C			
Boiling Point Range	Not available	Freezing point	Not available			
Evaporation Rate	Not available	Flammability (solid, gas)	Not applicable.			
Autoignition Temperature	307 °C (584.6 °F)	Flash Point	>145 °C (293 °F)			
Lower Explosive Limit	>=0.8 % v/v	Decomposition temperature	Not available			
Upper Explosive Limit	<=7 % v/v	Vapor Pressure	Not available			
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available			
Water Solubility	(Insoluble)	Partition coefficient: n- octanol/water	Not available			
Viscosity	Not available	Kinematic viscosity	Not available			
Solubility (Other)	Not available	Density	7.27 lb/gal			
Physical Form	Liquid.	Molecular Weight	Not available			
OSHA Flammability Class	Not flammable	Volatile Organic Compounds (As regulated)	46.1 WT%; 3.35 lb/US gal 402 g/L – As per 40 CFR Part 41.100(s)			

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Ρ /17

age 4 of 8	Rev. 04/1
------------	-----------

SDS ID: 820256

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS FORA™- Form Oil Release Agent

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid flames, sparks and other sources of ignition

Incompatible Materials

Acids, strong oxidizing materials, (chlorine, concentrated oxygen, sodium hypochlorite, calcium hypochlorite)

Hazardous decomposition products

None under normal temperatures and pressures.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Skin Contact

Prolonged or repeated exposure may cause skin dryness or cracking.

Eye Contact

No information on significant adverse effects.

Ingestion

May be harmful if swallowed.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Petroleum distillates, hydrotreated light naphthenic (64742-53-6)

Oral LD50 Rat >5000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >2000 mg/kg (no deaths occurred) Inhalation LC50 Rat 2180 mg/m3 4 h

Product Toxicity Data

Acute Toxicity Estimate

Not available.

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

May cause slight skin and respiratory irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No information on significant adverse effects.

Page 5 of 8 Rev. 04/17

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS FORA™- Form Oil Release Agent

Specific Target Organ Toxicity - Repeated Exposure

No information on significant adverse effects.

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

SDS ID: 820256

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Avoid release to the environment.

Component Analysis - Aquatic Toxicity

Petroleum distillates, hydrotreated light naphthenic	64742-53-6				
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L				
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID				

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

This product, if discarded, is not expected to be a characteristic or listed hazardous waste. If recycled in the USA, it can be managed in accordance with the used oil exemption under 40 CFR Part 279. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of this product.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transport.

TDG Information: Not regulated for transport.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Page 6 of 8 Rev. 04/17

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS FORA™- Form Oil Release Agent

Section 15 - REGULATORY INFORMATION

SDS ID: 820256

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactivity: No

Component Analysis - Inventory

Petroleum distillates, hydrotreated light naphthenic (64742-53-6)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR KECI - Annex 1		KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	No	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Summary of Changes

Revision to comply with WHMIS 2015.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC – European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP -

Page 7 of 8 Rev. 04/17

Material Name: SAFETY-KLEEN PROFESSIONAL PRODUCTS FORA™- Form Oil Release Agent

Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM -ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL -Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA -National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA -Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA -United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS -Workplace Hazardous Materials Information System (Canada).

SDS ID: 820256

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Page 8 of 8 Rev. 04/17