



## **KLEEN+RHT70**

KLEEN+ RHT70 Base Oil is part of our advanced base oil line redefining quality and sustainability in the industry. Our premium KLEEN+RHT70 base oil now delivers best-in-class API Group II base oil performance for reduced formulating costs and premium finished fluid quality. KLEEN+ RHT70 delivers top tier cold temperature performance, low volatility and premium oxidation performance and is excellent where premium light grade lubricants are required. It provides premium performance in all types of lighter viscosity formulations or as a blend component in higher viscosity formulations. It performs great in applications requiring superior solubilization characteristics (polymers, additives etc.).

KLEEN+ RHT70 base oil is manufactured at multiple state-of-the-art refineries across the US and Canada resulting in improved reliability, increased security, and continuity of supply. The base oil production at all our sites undergo a battery of tests and pass stringent quality controls to ensure that base oils produced using our proprietary processes do not need corrector fluids.

## **Typical Properties**

| KLEEN+                                     | Test Method              | RHT70          |  |
|--|--------------------------|----------------|--|
| Kinematic Viscosity cSt @ 40°C cSt @ 100°C | ASTM D7279<br>ASTM D7279 | 12.7<br>3.1    |  |
| Viscosity Index                            | ASTM D2270               | 103            |  |
| Color                                      | ASTM D1500               | L 0.5          |  |
| Appearance                                 | Visual                   | Clear & Bright |  |
| Specific Gravity @ 15°C (60°F)             | ASTM D4052               | 0.846          |  |
| Flash Point, °C                            | ASTM D92                 | 185            |  |
| Pour Point, °C                             | ASTM D5949               | -21            |  |
| Cold-Cranking Simulator @ -25°C, cP        | ASTM D5293               | 575            |  |
| Sulfur, μg/g                               | ASTM D5185               | < 50           |  |

Note: Values shown above are representative of current production and may vary within modest ranges.

## New Baseline in Base Oils

Reliability: KLEEN+ base oils are built on the foundation that superior base oils produce superior finished goods, so we start with a better feedstock to produce a better base oil. As the largest provider of re-refined base oil in North America, the Automotive, Heavy Duty, and Industrial sectors requiring high-quality Group II, Group II+, and Group III paraffinic base oil rely on the quality, security, and advantages.

Quality: KLEEN+ base oils redefine quality due to the feedstock and our proprietary refining processes to deliver base oils which best the competition. Our KLEEN+ Base Oils are tested, proven and trusted. Companies rely on our quality and performance Kleen+ Base Oils that are superior to Group II base oils derived from crude. No other company can match our top-quality Group II+ and re-refined Group III base oils.

Sustainability: Using KLEEN+ Base Oils means less reliance on natural resources. It's better for the environment, plays a significant role in sustainability efforts and it is better to the bottom line.

All company, product and service names inclusive of product and brand names are property of Safety-Kleen, a Clean Harbors Company.