

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

# **Section 1 - PRODUCT AND COMPANY IDENTIFICATION**

#### **Material Name**

ECOPOWER DIESEL ENGINE OIL Includes Grades 10W-30, 15W-40, 30, 40, 50

**Product Code** 

Prefix 22

**Synonyms** 

Petroleum oil; lube oil; petroleum hydrocarbon; lubricant.

### **Product Use Recommended Use**

For lubricating diesel engines. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

#### **Restrictions on Use**

None known.

#### MANUFACTURER/SUPPLIER

Safety-Kleen Systems, Inc. 2600 North Central Expressway Suite 200 Richardson, TX 75080 www.safety-kleen.com

#### IMPORTER/DISTRIBUTOR

Safety-Kleen Canada, Inc. 25 Regan Road Brampton, Ontario, Canada L1A 1B2

SDS ID: 820095

Phone: 1-800-669-5740 Emergency Phone #: 1-800-468-1760

**Issue Date** 

April 15, 2017

**Supersedes Issue Date** 

November 16, 2015

**Original Issue Date** 

October 22, 2012

### **Section 2 - HAZARDS IDENTIFICATION**

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

Not hazardous according to classification criteria.

### **GHS Label Elements**

Symbol(s)

None needed according to classification criteria.

### Signal Word

None needed according to classification criteria.

### **Hazard Statement(s)**

None needed according to classification criteria.

SDS ID: 820095

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

### **Precautionary Statement(s)**

#### **Prevention**

None needed according to classification criteria.

#### Response

None needed according to classification criteria.

#### Storage

None needed according to classification criteria.

### **Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Other hazards

Repeated exposure may cause skin dryness or cracking. When aerosolizing, misting, or heating these products, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	35-85
72623-83-7	Lubricating oils, petroleum, C>25, hydrotreated bright stock-based	0.1-55
64742-62-7	Residual oils (petroleum), solvent dewaxed	0.1-55
64742-57-0	Residual oils, petroleum, hydrotreated	0.1-55
64742-01-4	Residual oils, petroleum, solvent-refined	0-46
Not Available	Mineral oil	0.1-37.5
Not Available	Proprietary additives	10-30
64741-88-4	Distillates, petroleum, solvent-refined heavy paraffinic	1-15
122-39-4 Diphenylamine		1-15
72623-86-0	Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	0.1-11
	Mixture*	0-5

#### **Additional information**

\*Mixture of the following CAS #s: Poly olefin, 64742-65-0, Polyolefin amide alkene amine, 64742-52-5, 178603-65-1, 178603-64-0, 64742-46-7, 72623-84-8, 178603-63-9, 178603-66-2, 72623-87-1, 8042-47-5, 445411-73-4, Calcium sulfonate, Alkylated phenol, Alkylamine, 74499-35-7, 68411-46-1, 68649-42-3, Calcium phenate, 72623-85-9

# **Section 4 - FIRST AID MEASURES**

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention if needed.

Page 2 of 10 Rev. 04/17

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if needed.

**Eyes** 

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get medical attention if needed.

SDS ID: 820095

**Ingestion** 

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

### **Most Important Symptoms/Effects**

Acute

No information on significant adverse effects.

**Delayed** 

Repeated exposure may cause dryness or cracking.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident.

### **Section 5 - FIRE FIGHTING MEASURES**

#### **Extinguishing Media**

### **Suitable Extinguishing Media**

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

### **Unsuitable Extinguishing Media**

Do not use high-pressure water streams.

#### **Special Hazards Arising from the Chemical**

Negligible fire hazard.

### **Hazardous Combustion Products**

Burning may produce smoke, carbon dioxide, carbon monoxide, unidentified organic compounds, metal oxides, nitrogen oxides, hydrogen sulfide, sulfur oxides, oxides of phosphorus, and oxides of zinc.

### **Special Protective Equipment and Precautions for Firefighters**

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

#### **Fire Fighting Measures**

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry.

### **Section 6 - ACCIDENTAL RELEASE MEASURES**

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

#### Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

Page 3 of 10 Rev. 04/17

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

# **Section 7 - HANDLING AND STORAGE**

### **Precautions for Safe Handling**

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with: Skin, eyes, clothing, shoes. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use Personal Protective equipment as required.

SDS ID: 820095

### Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

### **Incompatible Materials**

Acids, oxidizing materials.

### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**Component Exposure Limits** 

Diphenylamine	122-39-4			
Alberta, British Columbia, Manitoba, New Brunswick, Nova Scotia, Ontario, Prince Edward Island	10 mg/m3 TWA			
Northwest Territories, Nunavut, Saskatchewan, Yukon	10 mg/m3 TWA; 20 mg/m3 STEL			
Nova Scotia	10 mg/m3 TWA			
Quebec	10 mg/m3 TWAEV			
ACGIH	10 mg/m3 TWA			

### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

#### **Engineering Controls**

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

# Individual Protection Measures, such as Personal Protective Equipment Eve/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

# **Respiratory Protection**

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions

Page 4 of 10 Rev. 04/17

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

SDS ID: 820095

#### **Glove Recommendations**

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber (latex), polyvinyl chloride (PVC) or equivalent gloves is not recommended. To avoid prolonged or repeated contact with product where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

#### **Protective Materials**

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Gloves, safety glasses, and lab coat or apron.

### **Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Amber liquid	Physical State	Liquid
Odor	Petroleum odor	Color	Amber
Odor Threshold	Not available	рН	Not available
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	246 °C (475 °F)
<b>Boiling Point Range</b>	Not available	Freezing point	Not available
<b>Evaporation Rate</b>	0.1 (butyl acetate = 1)	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	216 °C (421°F)[Cleveland Open Cup]
<b>Lower Explosive Limit</b>	Not available	<b>Decomposition temperature</b>	Not available
<b>Upper Explosive Limit</b>	Not available	Vapor Pressure	<0.1 mm Hg@20°C(68°F)
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.88
Water Solubility	(Insoluble )	Partition coefficient: n- octanol/water	Not available
Viscosity	>20.5 mm <sup>2</sup> /s 40°C (104 °F)	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	7.4 lb/gal
Physical Form	liquid	Volatile Organic Compounds (As regulated)	Negligible; Per 40 CFR Part 51.100(s)
Molecular Weight	Not available		

### **Section 10 - STABILITY AND REACTIVITY**

### Reactivity

No reactivity hazard is expected.

### **Chemical Stability**

Stable under normal temperatures and pressures.

Page 5 of 10 Rev. 04/17

SDS ID: 820095

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

#### **Possibility of Hazardous Reactions**

Will not polymerize.

#### **Conditions to Avoid**

Avoid sparks, flame, and other sources of ignition.

#### **Incompatible Materials**

Acids, oxidizing materials.

#### **Hazardous decomposition products**

None under normal temperatures and pressures.

### Section 11 - TOXICOLOGICAL INFORMATION

#### **Information on Likely Routes of Exposure**

#### Inhalation

No information on significant adverse effects.

#### **Skin Contact**

Prolonged or repeated exposure may cause skin dryness or cracking.

#### **Eve Contact**

No information on significant adverse effects.

#### **Ingestion**

May be harmful if swallowed.

#### **Acute and Chronic Toxicity**

### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

#### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >4480 mg/kg

### Lubricating oils, petroleum, C>25, hydrotreated bright stock-based (72623-83-7)

Oral LD50 Rat >5000 mg/kg

#### Residual oils (petroleum), solvent dewaxed (64742-62-7)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h

### Residual oils, petroleum, solvent-refined (64742-01-4)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h

### Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat >5530 mg/m3 4 h (no deaths occurred )

### Diphenylamine (122-39-4)

Oral LD50 Rat 1120 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

### Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h

### **Product Toxicity Data**

### **Acute Toxicity Estimate**

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

#### Immediate Effects

No information on significant adverse effects.

### **Delayed Effects**

No information on significant adverse effects.

Page 6 of 10 Rev. 04/17

SDS ID: 820095

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

#### **Irritation/Corrosivity Data**

May cause slight skin and respiratory irritation.

### **Respiratory Sensitization**

No information for the product.

### **Dermal Sensitization**

No information for the product.

#### **Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

### **Germ Cell Mutagenicity**

No information available for the product.

### **Tumorigenic Data**

No information available for the product.

#### **Reproductive Toxicity**

No information available for the product.

### **Specific Target Organ Toxicity - Single Exposure**

No information on significant adverse effects.

### Specific Target Organ Toxicity - Repeated Exposure

No information available on significant adverse effects.

### **Aspiration hazard**

No data available.

#### **Medical Conditions Aggravated by Exposure**

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

#### **Additional Data**

No additional information is available.

### **Section 12 - ECOLOGICAL INFORMATION**

## **Component Analysis - Aquatic Toxicity**

Lubricating oils, petroleum, hydrotreated spent	64742-58-1				
Fish:	LC50 96 h Brachydanio rerio 79.6 mg/L [semi-static]; LC50 96 h Pimephales promelas 3.2 mg/L [semi-static]				
Lubricating oils, petroleum, C>25, hydrotreated bright stock-based	72623-83-7				
Fish:	LC50 96 h Lepomis macrochirus >10000 mg/L				
Residual oils (petroleum), solvent dewaxed	64742-62-7				
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L				
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID				
Residual oils, petroleum, solvent-refined	64742-01-4				
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L				
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID				

Page 7 of 10 Rev. 04/17

SDS ID: 820095

# Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4				
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L				
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID				
Diphenylamine	122-39-4				
Fish:	LC50 96 h Pimephales promelas 3.47 - 4.14 mg/L [flow-through]				
Algae:	EC50 72 h Scenedesmus subspicatus 1.5 mg/L IUCLID				
Invertebrate:	EC50 48 h Daphnia magna 1.69 - 2.46 mg/L EPA				
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0				
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L				
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID				

### **Persistence and Degradability**

No information available for the product.

### **Bioaccumulative Potential**

No information available for the product.

### **Mobility**

No information available for the product.

#### Other Toxicity

No additional information is available.

# **Section 13 - DISPOSAL CONSIDERATIONS**

### **Disposal Methods**

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

### **Section 14 - TRANSPORT INFORMATION**

**US DOT Information:** Not regulated for transport. **IATA Information:** Not regulated for transport. **IMDG Information:** Not regulated for transport. **TDG Information:** Not regulated for transport.

International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Diphenylamine	122-39-4
---------------	----------

Page 8 of 10 Rev. 04/17

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

IBC Code:	Category Y (molten )
-----------	----------------------

### **Section 15 - REGULATORY INFORMATION**

SDS ID: 820095

#### **Canada Regulations**

#### **CEPA - Priority Substances List**

None of this product's components are on the list.

### **Ozone Depleting Substances**

None of this product's components are on the list.

### Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

#### Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

### **U.S. Federal Regulations**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Diphenylamine	122-39-4
SARA 313:	1 % de minimis concentration

### SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: No Chronic Health: No Fire: No Pressure: No Reactivity: No

#### **Component Analysis - Inventory**

Lubricating oils, petroleum, hydrotreated spent (64742-58-1), Residual oils (petroleum), solvent dewaxed (64742-62-7), Residual oils, petroleum, hydrotreated (64742-57-0), Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4), Diphenylamine (122-39-4), Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	REACH	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	Yes	Yes

Lubricating oils, petroleum, C>25, hydrotreated bright stock-based (72623-83-7), Residual oils, petroleum, solvent-refined (64742-01-4)

US	CA	EU	AU	PH	JP - ENCS		KR KECI - Annex 1		REACH	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	No	Yes

Page 9 of 10 Rev. 04/17

Material Name: ECOPOWER DIESEL ENGINE OIL

Includes Grades 10W-30, 15W-40, 30, 40, 50

# **Section 16 - OTHER INFORMATION**

NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Summary of Changes** 

2017-06-05: Minor corrections to Section 2.

#### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CFR -Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC -European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F -Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH -Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP -Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts<sup>TM</sup> -ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL -Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA -National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA -Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA -United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS -Workplace Hazardous Materials Information System (Canada).

### Other Information

#### Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Rev. 04/17

Page 10 of 10	ĺ
---------------	---

SDS ID: 820095