



## Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Part B

SDS ID: 82977

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name**

ArmaKleen Paint and Ink Remover: Part B

**Product Code**

6364, 6464

Formula Code 42000129

**Synonyms**

Not available.

**Product Use**

Water-based paint and ink remover that is one part of a two part coating removal process. This is designed to remove paints and inks from aluminum and steel. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

**Restrictions on Use**

For professional use only.

**MANUFACTURER**

Church & Dwight  
The ArmaKleen™ Company  
469 North Harrison Street  
Princeton, NJ 08543  
Phone: (800) 332-5424  
[www.churchdwight.com](http://www.churchdwight.com)

**SUPPLIER (in the U.S.A.)**

Safety-Kleen Systems, Inc.  
42 Longwater Drive  
Norwell, MA 02061-9149  
U.S.A.  
Phone: 1-800-669-5740  
[www.safety-kleen.com](http://www.safety-kleen.com)

**SUPPLIER (in Canada)**

Safety-Kleen Canada Inc.  
25 Regan Road  
Brampton, Ontario, L7A 1B2  
Canada  
Phone: 1-800-669-5740

**Emergency Telephone Number**

Medical: 1-888-234-1828 Chemical: 1-800-255-3924 (CHEMTEL)

**Issue Date**

May 5, 2021

**Supersedes Issue Date**

March 21, 2021

**Original Issue Date**

September 1, 2004

### Section 2 - HAZARDS IDENTIFICATION

**Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States**

Skin Corrosion/Irritation - Category 1A

Serious Eye Damage/Eye Irritation - Category 1

Skin Sensitization - Category 1A

Specific Target Organ Toxicity - Repeated Exposure - Category 2

# Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Part B

SDS ID: 82977

## GHS Label Elements

### Symbol(s)



### Signal Word

Danger.

### Hazard Statement(s)

Causes severe skin burns and eye damage.

May cause allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

### Precautionary Statement(s)

#### Prevention

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product.

#### Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

#### Storage

Store locked up. Do not store below 40°F (4.4°C).

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Other hazards

Repeated exposure may cause skin dryness or cracking. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
7732-18-5	Water	76-84
124-68-5	2-Amino-2-methyl-1-propanol	12-13
1300-72-7	Sodium xylenesulfonate	0.95-1.05
23783-26-8	Acetic acid, hydroxyphosphono-	0.24-0.26

# Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Part B

SDS ID: 82977

## Section 4 - FIRST AID MEASURES

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor.

### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse.

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

### Ingestion

IF SWALLOWED: Rinse mouth. If swallowed, do NOT induce vomiting. Immediately call a POISON CENTER or doctor.

### Most Important Symptoms/Effects

#### Acute

Causes skin burns, eye burns, an allergic skin reaction. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

#### Delayed

Repeated exposure may cause skin dryness or cracking.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively. Possible mucosal damage may contraindicate the use of gastric lavage.

## Section 5 - FIRE FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, water fog.

#### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

### Special Hazards Arising from the Chemical

Negligible fire hazard.

### Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide, nitrogen oxide, sulfur oxides.

### Advice for firefighters

Containers may rupture if heated or exposed to continual naked flame.

### Fire Fighting Measures

Move container from fire area if it can be done without risk. Keep storage containers cool with water spray. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

### Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

# Safety Data Sheet

**Material Name: ArmaKleen Paint and Ink Remover: Part B**

**SDS ID: 82977**

Spilled product is slippery. Do not touch or walk through spilled product. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

## Section 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

Keep away from naked flame. Do not breathe dust or vapors. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

### Conditions for Safe Storage, Including any Incompatibilities

Store locked up. Do not store below 40°F (4.4°C).

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from naked flame.

Empty product containers may retain product residue and can be dangerous.

### Incompatible Materials

Avoid oxidizing agents and reducing agents, May react on contact with strong acids.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component Exposure Limits

Canada and ACGIH have not developed exposure limits for any of this product's components.

### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

### Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

#### Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

#### Skin Protection/Glove Recommendations

Where skin contact is likely, wear gloves impervious to product; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits or other protective clothing.

#### Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, Lab coat or apron.

# Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Part B

SDS ID: 82977

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Light amber clear liquid	<b>Physical State</b>	Liquid
<b>Odor</b>	Characteristic	<b>Color</b>	Amber
<b>Odor Threshold</b>	Not available	<b>pH</b>	11.5 (aqueous solution )
<b>Melting Point</b>	21.20°F (-6 °C)	<b>Boiling Point</b>	212°F (100 °C)
<b>Boiling Point Range</b>	Not available	<b>Freezing point</b>	Not available
<b>Evaporation Rate</b>	(equal to water. )	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition Temperature</b>	Not available	<b>Flash Point</b>	> 212°F (100 °C)
<b>Lower Explosive Limit</b>	Not available	<b>Decomposition temperature</b>	Not available
<b>Upper Explosive Limit</b>	Not available	<b>Vapor Pressure</b>	Not available
<b>Vapor Density (air=1)</b>	Not available	<b>Specific Gravity (water=1)</b>	1.01
<b>Water Solubility</b>	(complete )	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	Not available	<b>Kinematic viscosity</b>	Not available
<b>Solubility (Other)</b>	Not available	<b>Density</b>	Not available
<b>Molecular Weight</b>	Not available		
<b>Volatile Organic Compounds (As Regulated)</b>	14.5 WT%; 1.22 LB/US gal; 146 g/L; As per 40 CFR Part 51.100(s) VOC Composite Partial Pressure @20°C = 0.002 mmHg Consult with your state/local air pollution control agency and their rules/regulations for specific direction in your specific area.		

## Section 10 - STABILITY AND REACTIVITY

### Reactivity

May react on contact with strong acids.

### Chemical Stability

Stable under normal temperatures and pressures.

### Possibility of Hazardous Reactions

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

### Conditions to Avoid

Avoid naked flame and direct sunlight.

### Incompatible Materials

Avoid oxidizing agents, reducing agents, strong acids.

### Hazardous decomposition products

Oxides of Carbon, Nitrogen and Sulfur. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

### Thermal decomposition products

Carbon monoxide. Nitrogen oxides (NOx). Hydrogen. sulfur oxides.

# Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Part B

SDS ID: 82977

## Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

#### Inhalation

May cause irritation.

#### Skin Contact

Causes burns. May cause allergic skin reaction.

#### Eye Contact

Causes eye burns.

#### Ingestion

May cause irritation.

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

##### 2-Amino-2-methyl-1-propanol (124-68-5)

Oral LD50 Rat 2900 mg/kg (in physiological saline); Dermal LD50 Rabbit >2000 mg/kg (no deaths occurred)

##### Sodium xylenesulfonate (1300-72-7)

Oral LD50 Rat 1000 mg/kg

### Product Toxicity Data

#### Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

### Immediate Effects

Causes burns, eye burns, skin burns. May cause allergic skin reaction. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

### Delayed Effects

Repeated exposure may cause skin dryness or cracking.

### Irritation/Corrosivity Data

Causes burns. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

### Respiratory Sensitization

Based on best current information, there is no known human sensitization associated with this product.

### Dermal Sensitization

May cause allergic skin reaction.

### Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

### Germ Cell Mutagenicity

Based on best current information, there is no known teratogenicity associated with this product.

Experimental evidence suggests that this product does not cause mutagenesis.

### Tumorigenic Data

No data available

### Reproductive Toxicity

Based on best current information, there is no known reproductive toxicity associated with this product.

### Specific Target Organ Toxicity - Single Exposure

No target organs identified.

### Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

Based on available data, the classification criteria are not met.

# Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Part B

SDS ID: 82977

## Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

## Section 12 - ECOLOGICAL INFORMATION

### Component Analysis - Aquatic Toxicity

<b>2-Amino-2-methyl-1-propanol</b>	<b>124-68-5</b>
Fish:	LC50 96 h <i>Lepomis macrochirus</i> 190 mg/L [static ]
Algae:	EC50 72 h <i>Desmodesmus subspicatus</i> 520 mg/L IUCLID
Invertebrate:	EC50 48 h <i>Daphnia magna</i> 193 mg/L IUCLID

### Invertebrate Toxicity

No additional information is available.

### Persistence and Degradability

No information available for the product.

### Bioaccumulative Potential

No information available for the product.

### Mobility

No information available for the product.

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact ArmaKleen regarding proper recycling or disposal.

## Section 14 - TRANSPORT INFORMATION

### US DOT Information:

**Shipping Name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , (Contains: amines )

**Hazard Class:** 8

**UN/NA #:** UN3267

**Packing Group:** III

**Required Label(s):** 8

### IATA Information:

**Shipping Name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ( Contains: amines )

**Hazard Class:** 8

**UN#:** UN3267

**Packing Group:** III

**Required Label(s):** 8

### IMDG Information:

**Shipping Name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ( Contains: amines )

**Hazard Class:** 8

**UN#:** UN3267

# Safety Data Sheet

Material Name: ArmaKleen Paint and Ink Remover: Part B

SDS ID: 82977

**Packing Group:** III  
**Required Label(s):** 8

**TDG Information:**

**Shipping Name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ( Contains: Contains Sodium hydroxide , Sodium silicate )

**Hazard Class:** 8

**UN#:** UN3267

**Packing Group:** III

**Required Label(s):** 8

**International Bulk Chemical Code**

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

<b>2-Amino-2-methyl-1-propanol</b>	<b>124-68-5</b>
IBC Code:	Category Z

## Section 15 - REGULATORY INFORMATION

**Canada Regulations**

**CEPA - Priority Substances List**

None of this product's components are on the list.

**Ozone Depleting Substances**

None of this product's components are on the list.

**Council of Ministers of the Environment - Soil Quality Guidelines**

None of this product's components are on the list.

**Council of Ministers of the Environment - Water Quality Guidelines**

None of this product's components are on the list.

**U.S. Federal Regulations**

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

**SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories**

**Acute Health:** Yes **Chronic Health:** No **Fire:** No **Pressure:** No **Reactivity:** No

**U.S. State Regulations**

**2-Amino-2-methyl-1-propanol (124-68-5), Sodium xylene sulfonate (1300-72-7), Acetic acid, hydroxyphosphono- (23783-26-8)**

<b>MA</b>	<b>NJ</b>	<b>PA</b>
Yes	Yes	Yes

**Not listed under California Proposition 65.**



# Safety Data Sheet

**Material Name: ArmaKleen Paint and Ink Remover: Part B**

**SDS ID: 82977**

## Component Analysis - Inventory

### 2-Amino-2-methyl-1-propanol (124-68-5)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

### Sodium xylenesulfonate (1300-72-7)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			Yes	Yes	Yes	Yes	Yes	Yes

### Acetic acid, hydroxyphosphono- (23783-26-8)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	ELN	No	Yes	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			No	Yes	Yes	Yes	Yes	Yes

## Section 16 - OTHER INFORMATION

### Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR).

### NFPA Ratings

Health: 3 Fire: 0 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Summary of Changes

Update to chemical emergency phone number and VOC information. **Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD

# Safety Data Sheet

**Material Name: ArmaKleen Paint and Ink Remover: Part B**

**SDS ID: 82977**

- Dangerous Substance Directive; DSL - Domestic Substances List; EC – European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; Ne- Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL – Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

## **Other Information**

### **Disclaimer:**

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, ArmaKleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.