



RHT Base Oil Viscosity Grades Less Than 110

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 02/03/2023

Date of Issue: 09/29/1988

Supersedes Date: 06/13/2022

Version: 1.3

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Substance

Product Name: KLEEN+™ RHT Base Oil Viscosity Grades Less Than 110

CAS-No.: 64742-58-1

Product Code: Prefix 08

Synonyms: Petroleum oil; lube oil; petroleum hydrocarbon; lubricant.

SDS No.: 820169

1.2. Intended Use of the Product

Lubricating oils.

1.3. Name, Address, and Telephone of the Responsible Party

For Product Manufactured in U.S.A.:

Manufacturer

Safety-Kleen Systems, Inc.

42 Longwater Drive

Norwell, MA 02061-9149

U.S.A

Supplier (in Canada)

Safety-Kleen Canada, Inc.

25 Regan Road

Brampton, Ontario, Canada L7A 1B2

For Product Manufactured in Canada:

Manufacturer

Safety-Kleen Canada, Inc.

25 Regan Road

Brampton, Ontario, Canada L7A 1B2

Supplier (in U.S.A)

Safety-Kleen Systems, Inc.

42 Longwater Drive

Norwell, MA 02061-9149

U.S.A

www.safety-kleen.com

Phone: 1-800-669-5740

1.4. Emergency Telephone Number

Emergency Number : 1-800-468-1760

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Asp. Tox. 1 H304

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA) :



GHS08

Signal Word (GHS-US/CA) :

Danger

Hazard Statements (GHS-US/CA) :

H304 - May be fatal if swallowed and enters airways.

Precautionary Statements (GHS-US/CA) :

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

KLEEN+ RHT Base Oil Viscosity Grades Less Than 110

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Lubricating oils, petroleum, hydrotreated spent	Lubricating oils (petroleum), hydrotreated spent / Oils, lubricating, (petroleum), hydrotreated spent / Lubricating oils (petroleum) hydrotreated spent / Lubricating oils, petroleum, hydrotreated, spent / Lubricating oils, petroleum, hydrotreated spent (A complex combination of hydrocarbons obtained by treating a spent lube oil with hydrogen in the presence of a catalyst. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15-50.)	(CAS-No.) 64742-58-1	80-100	Asp. Tox. 1, H304

Full text of H-statements: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%). The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

3.2. Mixture

Not applicable

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Wash with plenty of soap and water. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Immediately call a POISON CENTER or doctor/physician. Place affected person on their side. Rinse mouth. Do NOT induce vomiting.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May be fatal if swallowed and enters airways.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical, foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use water.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

KLEEN+ RHT Base Oil Viscosity Grades Less Than 110

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Aldehydes. Ketones. Unidentified organic compounds.

Other Information: No additional information available.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, spray). Spilled material may present a slipping hazard.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a large spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Lubricating oils

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Mineral oils		
USA ACGIH	ACGIH OEL TWA	5 mg/m ³ Pure, highly and severely refined: 5 mg/m ³ TWA (inhalable particulate matter). Poorly and mildly refined:

KLEEN+ RHT Base Oil Viscosity Grades Less Than 110

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		Exposure by all routes should be carefully controlled to levels as low as possible.
USA OSHA	OSHA PEL (TWA) [1]	5 mg/m ³
USA NIOSH	NIOSH REL (TWA)	5 mg/m ³
Alberta	OEL TWA	5 mg/m ³
British Columbia	OEL TWA	1 mg/m ³ Severely refined [0.2 mg/m ³ for mildly refined oils]
Manitoba	OEL TWA	5 mg/m ³ ACGIH Value
Newfoundland & Labrador	OEL TWA	5 mg/m ³ ACGIH
Nova Scotia	OEL TWA	5 mg/m ³ ACGIH
Nunavut	OEL STEL	10 mg/m ³
Nunavut	OEL TWA	5 mg/m ³
Northwest Territories	OEL STEL	10 mg/m ³
Northwest Territories	OEL TWA	5 mg/m ³
Ontario	OEL TWA	5 mg/m ³ Pure, highly and severely refined
Québec	VECD (OEL STEL)	10 mg/m ³
Québec	VEMP (OEL TWA)	5 mg/m ³
Saskatchewan	OEL STEL	10 mg/m ³
Saskatchewan	OEL TWA	5 mg/m ³
Yukon	OEL STEL	10 mg/m ³
Yukon	OEL TWA	5 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Safety glasses with side-shields. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Safety glasses with side-shields.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Amber
Odor	: petroleum
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: ≥ 260.8 °C (501.4°F)
Flash Point	: ≥ 165 °C (329°F)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available

KLEEN+ RHT Base Oil Viscosity Grades Less Than 110

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: < 0.1 mm Hg @ 20 °C (68°F)
Relative Vapor Density at 20°C	: No data available
Relative Density	: 0.87 (Water = 1)
Density	: ≈ 7.1 lb/gal
Specific Gravity	: No data available
Solubility	: Water: Insoluble
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: < 20.5 mm ² /s 40 °C (104 °F)
VOC content	: Negligible; As per 40 CFR CFR Part 51.100(s)

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides (CO, CO₂). Aldehydes. Ketones. Unidentified organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 4480 mg/kg

KLEEN+ RHT Base Oil Viscosity Grades Less Than 110

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

12.2. Persistence and Degradability

Safety-Kleen RHT Base Oil Viscosity Grades Less Than 110 (64742-58-1)

Persistence and Degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative Potential

Safety-Kleen RHT Base Oil Viscosity Grades Less Than 110 (64742-58-1)

Bioaccumulative Potential	Not established.
---------------------------	------------------

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Treatment Methods: Consult supplier for specific recommendations.

Sewage Disposal Recommendations: Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Safety-Kleen RHT Base Oil Viscosity Grades Less Than 110 (64742-58-1)

SARA Section 311/312 Hazard Classes	Health hazard - Aspiration hazard
-------------------------------------	-----------------------------------

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.2. US State Regulations

Neither this product nor its chemical components appear on any US state lists, or its chemical components are not required to be disclosed.

15.3. Canadian Regulations

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 02/03/2023

Indication of Changes : Review of data. Language modified.

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

KLEEN+ RHT Base Oil Viscosity Grades Less Than 110


Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

GHS Full Text Phrases:

Asp. Tox. 1	Aspiration hazard Category 1
H304	May be fatal if swallowed and enters airways

- NFPA Health Hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
- NFPA Fire Hazard : 1 - Materials that must be preheated before ignition can occur.
- NFPA Reactivity Hazard : 0 - Material that in themselves are normally stable, even under fire conditions.



The information contained herein is correct to the best of our knowledge, information, and belief and is designed only as guidance for the handling, use, processing, storage, transportation, disposal, and release of the product. User assumes all risks incident to use of this product and shall determine the quality and suitability of the product for its use. Supplier offers no warranty, express or implied, whatsoever, including warranties of merchantability or fitness for a particular purpose or otherwise, and specifically disclaims any and all liability for incidental, consequential, or other damages arising out the use or misuse of the product. The information provided relates only to the specific material provided and may not be valid if used in combination with any other materials or process, unless specified herein.

NA GHS SDS 2015 (Can, US)